

HydroSplash 4-Stage RO System

Four Stage RO with 50 GPD Membrane and proprietary twist-off filters.

The Charger HydroSplash is an undersink Reverse Osmosis filter system optimized to treat city water using the existing water pressure. This model makes up to 75 gallons a day of great tasting water while taking up less space than most other 4 and 5-stage models. Choose 4 or 5-stages of filtration to ensure premium water taste and quality. The easy twist-off disposable filter cartridges and RO membrane assembly are designed to make installation and replacement quick, easy and sanitary. Great for large service programs or for customers who like to do the filter replacement themselves. The HydroSplash comes complete, ready to install with connection hardware, tubing, faucet and instruction manual.

Features and Benefits:

- Proprietary twist-off filter cartridges
- High capacity 50 GPD TFC RO membrane assembly for easy replacement
- Quick connect o-ring seal fittings
- Compact size takes less space than most
 4 and 5-stage systems



SPECIFICATIONS

Shipping Weight: 24 lbs.

Dimensions: 14" L x 6" D x 15.5" H

Tank:

11" diameter x 15.5" H

CONDITIONS OF USE:

Water must be microbiologically safe

System Pressure: 40 min to 100 max psi

Temperature: 40 to 100° F

PH Range: 3 to 10

Turbidity: Less than 1.0 NTU

TDS:

1500 PPM max

Model: CWISO475PA/NF/CHPL

CERTIFIED REDUCED CONTAMINANTS:

Arsenic Copper Radium 226
Barium Fluoride & 228
Cadmium Lead Selenium
Chromium III Nitrate Turbidity
& VI Nitrite TDS



Tested for structural integrity, chemical extraction and reduction of contaminants.



HydroSplash 5-Stage RO System

Five Stage RO with 50 GPD Membrane and proprietary twist-off filters.

The Charger HydroSplash is an undersink Reverse Osmosis filter system optimized to treat city water using the existing water pressure. This model makes up to 75 gallons a day of great tasting water while taking up less space than most other 4 and 5-stage models. Choose 4 or 5-stages of filtration to ensure premium water taste and quality. The easy twist-off disposable filter cartridges and RO membrane assembly are designed to make installation and replacement quick, easy and sanitary. Great for large service programs or for customers who like to do the filter replacement themselves. The HydroSplash comes complete, ready to install with connection hardware, tubing, faucet and instruction manual.

Features and Benefits:

- Proprietary twist-off filter cartridges
- High capacity 50 GPD TFC RO membrane assembly for easy replacement
- Quick connect o-ring seal fittings
- Compact size takes less space than most
 4 and 5-stage systems



SPECIFICATIONS

Shipping Weight: 24 lbs.

Dimensions: 14" L x 6" D x 15.5" H

Tank:

11" diameter x 15.5" H

CONDITIONS OF USE:

Water must be microbiologically safe

System Pressure: 40 min to 100 max psi

Temperature: 40 to 100° F

PH Range: 3 to 10

Turbidity: Less than 1.0 NTU

TDS:

1500 PPM max

Model: CWISO575PA/NF/CHPL

CERTIFIED REDUCED CONTAMINANTS:

Arsenic Copper Radium 226
Barium Fluoride & 228
Cadmium Lead Selenium
Chromium III Nitrate Turbidity
& VI Nitrite TDS



Tested for structural integrity, chemical extraction and reduction of contaminants.