Programming Manual for IronBreaker III with WS1 10" x 54" Systems



- 1. From the time of day screen, press and hold the NEXT and down arrow buttons until the display changes.
- 2. Push the up arrow until you get to IRON FILTER and press NEXT.
- 3. Set the First Backwash to 10 minutes. Press NEXT.
- 4. Set Rinse for 8 minutes. Press NEXT.

CLOCK	NEXT		\Box	REGEN
-------	------	--	--------	-------

- 5. Set the Brine Draw to 40 minutes. Press NEXT.
- 6. Set the Second Backwash to OFF. Press NEXT.
- 7. Set the Pounds of Salt to OFF. Press NEXT.
- 8. If metered valve, set the Capacity to 5.0x1000. Press NEXT.
- 9. Set the Regen to OFF. Press NEXT.
- 10. Set the Relay to OFF. Press NEXT.
- 11. The Call setting can either be ignored or set to your preference. This setting will display CALL on the valve after a time period of your choosing to prompt the user to call for service. Press NEXT once you've got this set to your preference.
- 12. You should be at the time-of-day screen again. Press and hold the NEXT and up buttons until the display changes.
- 13. Set the Day Override to 3 DAYS. Press NEXT.
- 14. Set the Time of Regen to 12:30 AM. Press NEXT.
- 15. Set the Time of Day and the system is ready.

